

## CYG-GROUNDKIT-UNI Datasheet

## Grounding Kit, Standard Type, 5-26mm, 1 Meter





| Dimensions                    |  |
|-------------------------------|--|
| Bonding Conductor Length      | 1 m   39.37 in   |
| Lug Hole Size                 | M8   |
| Screw Size                    | M8x25  |
| Suitable Cable OD             | 5-26mm   |
| Environmental Specifications  |  |
| Operating Temperature         | -40°C to +70 °C (-40 °F to +158 °F)  |
| Weatherproofing Method        | Butyl and electric tape  |
| Electrical Specifications     |  |
| Contact Transition Resistance | Maximum 10mΩ   |
| Packaging and Weights         |  |
| Height, Packed                | 320 mm   12.60 in  |
| Width, Packed                 | 220 mm   8.66 in   |
| Included                      | Grounding kit   Hardware   Lug   One roll of PVC tape  <br>One roll of butyl rubber tape   Silicone grease |
| UOM                           | Kit  |
| Packaging                     | Bag  |
| Weight, Gross                 | 0.366 kg   0.806 lbs   |
| Certifications and Compliance |  |
| ISO 9001:2015                 | Designed, manufactured and/or distributed under this quality management system                             |
| RoHS                          | Compliant  |